Hoisting equipment Ratchet lever hoists



All ratchet lever hoists can be used for load attachment according to EN 12195.

Ratchet lever hoist model AL

Capacity 750 - 3000 kg

The enclosed housing, hand lever and hand wheel are made from high quality aluminium. Due to precise needle bearings the hoist can be operated with little effort. Its low tare weight is an advantage. When the hoist has to be frequently carried over longer distances to different assignments. This universal ratchet hoist should not be missing in any service truck. The chain guide is cast into the body to ensure faultless chain movement. The standard free chaining device serves to quickly attach the load or to pull the chain through the hoist in both directions.

Features

- Alloyed steel link chain with zinc-plated resp. yellow chromated finish, in accordance with national and international standards and regulations.
- Smooth running free chaining device as standard.
- Low effort on hand lever.




Yale hoists and trolleys are not designed for passenger elevation applications and must not be used for this purpose.

Technical data model AL										
Model	EAN-No. 4025092*	Capacity kg	Number of chain falls	Chain dimensions d x p mm	Lift with one full lever turn mm	Handle pull at WLL daN	Net weight at standard lift (3 m) kg			
AL 750	*051194	750	1	6.3 x 19.1	30	16	6.4			
AL 1000	*051200	1000	1	6.3 x 19.1	30	22	6.6			
AL 1500	*051217	1500	1	7.1 x 21.2	16	18	10.0			
AL 3000	*051224	3000	1	10 x 30.2	14	28	18.0			

Dimensions model AL

Model	AL 750	AL 1000	AL 1500	AL 3000
Amin., mm	315	325	380	455
B, mm	20	23	27	36
C, mm	22	23	26	33
D, mm	14	16	20	24
E, mm	300	300	300	400
F, mm	106	109	138	168
G, mm	47	47	60	75
H, mm	59	62	78	93
J, mm	154	154	177	212
K, mm	49	49	74	94
L, mm	105	105	103	118



Model AL

