


# Motorised lifting equipment for sport and cultural facilities



Designed according to  
the Directive Machines 2006/42/EC  
and the norm NF EN 14492-2.

## YOUR CONTACT:

Sales team

☎ : +33 (0) 344 511 133 - ✉ : [contact@huchez.fr](mailto:contact@huchez.fr)



# HUCHEZ

The quality of a French manufacturer

[huchez.com](http://huchez.com)





Handling solution for:

- Basketball blackboard and other retractable sport equipment
- Room partition
- Billboards (publicity...)
- ...

1



3 push buttons  
pendant control

2




AGON 300 kg  
electric winch

3



Fixed diverting pulley  
(ref. PF)

4



Articulated diverting pulley  
(ref. PA)

5



Complete wire rope kit  
with thimble loop and hook

6



320 kg fall arrester  
(ref. CHL-L).

# TECHNICAL CHARACTERISTICS



## ▶ 3 push buttons pendant control (Up – Down – Emergency stop).

- ▶ Plug and play.
- ▶ Wall mounted.
- ▶ Key locking.
- ▶ 20 m pendant control.



## ▶ AGON 300 kg electric winch.


- ▶ Compact (RAL grey 7031).
- ▶ Grooved drum.
- ▶ Good wire rope winding with the rope press role device.
- ▶ « Clock » limit switch device easy to set.
- ▶ Very low voltage pendant control (24 V) for a high protection against the electric risk of the operator.

Reference	AGON 300 kg
Capacity kg	300
Max. drum capacity m	16
Speed m/min	5.9
FEM	1Dm
Power	1Ph-230V



## ▶ Fixed diverting pulley with support plate (ref. PF).

- ▶ For 5 mm Ø wire rope.



## ▶ Articulated diverting pulley with support plate (ref. PA).

- ▶ For 5 mm Ø wire rope.
- ▶ Locking device to avoid the wire rope to go out of the sheave groove.



## ▶ Complete wire rope kit with timble loop and hook.

- ▶ Galvanised wire rope 5 mm Ø – Metallic central core 2170 N/mm<sup>2</sup> - Right hand or left hand lay according to the model.
- ▶ Wire rope length: 10, 15, 20 or 35 m.
- ▶ Single swivel hook.



## ▶ Fall arrester (ref. CHL-L 320 kg).

- ▶ Safety device to automatically stop the fall of a load.
- ▶ Yearly visual inspection. Maintenance by the manufacturer after activation.
- ▶ Wire rope length: 10 m.
- ▶ Integrated energy absorber reducing the stress on the reception structure.

QUOTE ON REQUEST.

Sales team

☎ : +33 (0) 344 511 133 - ✉ : [contact@huchez.fr](mailto:contact@huchez.fr)