



VDL - Universal steel drum clamp

For lifting of steel drums with rim in vertical or horizontal position. VDL is composed of a two-leg sling fitted with oval suspension ring and two clamps which are equipped with a system that pinches the rim of the drum.

- A unique clamp to lift and handle all sized steel drum (with rim)
- Clamp the drum in a horizontal or vertical position
- Working load limit up to 2,200 lbs (1,000 kg)

| Model | Item Number | Weight lbs. | Weight kg | WLL lbs. (t) | WLL kg | Drum dia. or length inches (min/max) | Drum dia. or length mm (min/max) |
|-------|-------------|-------------|-----------|--------------|--------|--------------------------------------|----------------------------------|
| VDL-1 | 54398 | 7.7 | 3.5 | 2,200 (1) | 1,000 | 6 / 37 1/2 | 150/950 |

F - Pipe hooks

Heavy duty hooks used in pairs for lifting horizontal pipes or tubes made of various materials.

- Easy to use
- Large range of capacities up to 33,000 lbs. (15,000 kg)
- Grade 80 or better chain slings are required but not provided

| Model | Item Number | Weight/pair lbs. | Weight/pair kg | WLL/pair lbs. | WLL/pair kg | Chain dia. in (mm) | Max opening in (mm) |
|-----------|-------------|------------------|----------------|---------------|-------------|--------------------|---------------------|
| F2 0-60 | 50118 | 8.8 | 4 | 4,400 | 2,000 | 5/16 (8) | 2 3/8 (60) |
| F5 0-75 | 50128 | 24.2 | 11 | 11,000 | 5,000 | 1/2 (13) | 3 (75) |
| F10 0-100 | 50138 | 52.8 | 24 | 22,000 | 10,000 | 5/8 (16) | 4 (100) |
| F15 0-100 | 50148 | 88 | 40 | 33,000 | 15,000 | 7/8 (20) | 4 (100) |



VLF - clamps for lifting welded steel drums with rim

For lifting of welded steel drums with rim, in vertical position. Can be used in combination with a lifting beam.

- Safety locking of the clamp on the drum
- Manual unlocking handle

| Model | Item Number | Weight lbs. | Weight kg | WLL lbs. | WLL kg | Drum dia. | Drum dia. |
|-----------|-------------|-------------|-----------|----------|--------|-----------|-----------|
| VLF05 600 | 51268 | 14.7 | 6.7 | 1,100 | 500 | 23 5/8" | 600 mm |
| VLF08 600 | 51278 | 21.1 | 9.6 | 1,750 | 800 | 23 5/8" | 600 mm |

All Topal™ clamps feature, a tested reliable design, are easy to use, and they all conform to ANSI B30.20 standards. New from Tractel® Griphoist® the name you Trust.

In the United States

Boston
1 800 421-0246
 51 Morgan Drive
 Norwood, MA 02062
 Tel. : (781) 401-3288
 Fax : (781) 828-3642
griphoist.usa@tractel.com

Los Angeles
1 800 675-6727
 365 Cloverleaf Dr., Suite D
 Baldwin Park, CA 91706
 Tel. : (626) 937-6727
 Fax : (626) 937-6730

DISTRIBUTED BY:



Griphoist® Division
www.tractel.com

In Canada

Montreal
1 800 561-3229
 11020 Mirabeau St.
 Montreal, Quebec H1J 2S3
 Tel. : (514) 493-3332
 Fax : (514) 493-3342
griphoist.canada@tractel.com

Tractel® Griphoist® is a
 ISO 9001 : 2008
 ISO 14001 : 2004
 OHSAS 18001 : 2007
 Certified Company

© Tractel®, Griphoist® P4105 NA Rev.1.12/2010

TOPAL™ LIFTING CLAMPS



Clamps compliant with ANSI B30.20



Griphoist® Division
www.tractel.com

KS multiposition plate clamps

A clamp range combining simplicity and flexibility, designed for lifting and revolving of plates, profiles, fabricated assemblies and steel frames during daily use.

- Lifting and revolving load with one clamp
- Clamping is secured by a spring mechanism
- The chain sling gives easy manipulation and positioning of the load
- Flexible clamping range fully usable without presetting
- Large oval suspension Ring

| Model | Item Number | Weight lbs. | Weight kg | WLL lbs. (t) | WLL kg | Opening inches | Opening mm |
|------------|-------------|-------------|-----------|--------------|--------|----------------|------------|
| KS075 0-15 | 50238 | 3.5 | 1.6 | 1,650 (3/4) | 750 | 0- 9/16 | 0-15 |
| KS1 0-20 | 50248 | 7.7 | 3.5 | 2,200 (1) | 1,000 | 0- 3/4 | 0-20 |
| KS2 0-25 | 50258 | 13.9 | 6.3 | 4,400 (2) | 2,000 | 0- 1 | 0-25 |
| KS3 0-30 | 50268 | 26.6 | 12.1 | 6,600 (3) | 3,000 | 0- 1 1/8 | 0-30 |





NX / NXR Automatic Non-Marring Clamp

The NX is designed for lifting and revolving without marring of smooth or polished pieces such as stainless steel plates, aluminum, pre-lacquered plates, wood, laminated sheets, marble, concrete, glass, plastic or any other fragile surface

- A clamp for all situations, with no risk of damaging the load
- For any rigid load up to 3,300 lbs (1500 kg) and 5 1/2" (140 mm) in thickness
- Permanently attached chain sling with a large oval suspension ring
- Non-marring Polyurethane coated jaws
- Automatic clamping (manual clamping recommended for fragile materials)

| Model | Item Number | Weight lbs. | Weight kg | WLL lbs. (t) | WLL kg | Opening inches | Opening mm |
|--------------|-------------|-------------|-----------|--------------|--------|----------------|------------|
| NX05 0-20 | 50408 | 9.9 | 4.5 | 1100 (0.5) | 500 | 0- 13/16 | 0- 20 |
| NXR05 0-100 | 50428 | 13.2 | 6 | 1100 (0.5) | 500 | 0- 4 | 0- 100 |
| NXR05 20-120 | 50438 | 12.8 | 5.8 | 1100 (0.5) | 500 | 13/16- 4 1/4 | 20- 120 |
| NXR05 40-140 | 50448 | 13.2 | 6 | 1100 (0.5) | 500 | 1 9/16- 5 1/2 | 40- 140 |
| NX1.5 0-30 | 50418 | 24 | 11 | 3,300 (1.5) | 1,500 | 0- 1 1/8 | 0- 30 |



KSA Plate clamp with ring

A clamp range combining simplicity and flexibility, designed for lifting plates during daily use.

- Reliable design, load fully secured and easy use
- Clamping is secured by a spring mechanism
- Flexible clamping range fully usable without presetting

| Model | Item Number | Weight lbs. | Weight kg | WLL lbs. (t) | WLL kg | Opening inches | Opening mm |
|-------------|-------------|-------------|-----------|--------------|--------|----------------|------------|
| KSA075 0-15 | 54768 | 3.3 | 1.5 | 1,650 (3/4) | 750 | 0- 9/16 | 0-15 |
| KSA1 0-20 | 54778 | 7.0 | 3.2 | 2,200 (1) | 1,000 | 0- 3/4 | 0-20 |



Curso Beam Clamps

Simple claw type beam clamp with a capacity up to 10 tons.

- Handle for simple and fast adjustments
- Compact sturdy construction
- Full range from 1 ton to 10 tons

| Model | Item Number | Weight lbs. | Weight kg | WLL lbs. (t) | WLL kg | Opening inches | Opening mm |
|--------|-------------|-------------|-----------|--------------|--------|----------------|------------|
| LT-1B | CC07009 | 10.6 | 4.8 | 2,200 (1) | 1,000 | 3 - 9 5/16 | 75 - 235 |
| LT-2B | CC07039 | 12.3 | 5.6 | 4,400 (2) | 2,000 | 3 - 9 7/16 | 75 - 240 |
| LT-3B | CC07049 | 24 | 11 | 6,600 (3) | 3,000 | 3.7 - 13 3/16 | 95 - 335 |
| LT-5B | CC07029 | 27.1 | 12.3 | 11,000 (5) | 5,000 | 3.7 - 13 | 95 - 330 |
| LT-10B | CC07019 | 46.3 | 21 | 22,000 (10) | 10,000 | 3.5 - 13 3/4 | 90 - 350 |

TLH – Horizontal Plate Clamp

The TLH is a horizontal lifting clamp that automatically adjusts to the load thickness by a pivoting actuator that secures every load by the lifting action of the clamp.

- Designed to be used in multiples of 2, 3 or 4 clamps according to load, sizing and shape.
- Loads up to 5 7/8 inches in thickness, including stacked plates
- Grade 80 or higher chain slings are required but not provided

| Model | Item Number | Weight* lbs. | Weight* kg | WLL* lbs. (t) | WLL* kg | Opening inches | Opening mm |
|-------------|-------------|--------------|------------|---------------|---------|----------------|------------|
| TLH1 0-60 | 51038 | 11 | 5 | 2,200 (1) | 1,000 | 0- 2 3/8 | 0- 60 |
| TLH1 0-120 | 51048 | 22 | 10 | 2,200 (1) | 1,000 | 0- 4 3/4 | 0-120 |
| TLH2 0-60 | 51058 | 22 | 10 | 4,400(2) | 2,000 | 0- 2 3/8 | 0- 60 |
| TLH2 0-120 | 51068 | 33 | 15 | 4,400 (2) | 2,000 | 0- 4 3/4 | 0-120 |
| TLH3 0-60 | 51078 | 25.5 | 11.6 | 6,600 (3) | 3,000 | 0- 2 3/8 | 0- 60 |
| TLH3 0-150 | 51088 | 58.5 | 26.6 | 6,600 (3) | 3,000 | 0- 5 7/8 | 0-150 |
| TLH4 0-60 | 51098 | 35.2 | 16 | 8,800 (4) | 4,000 | 0- 2 3/8 | 0- 60 |
| TLH4 0-150 | 51108 | 73.4 | 33.4 | 8,800 (4) | 4,000 | 0- 5 7/8 | 0-150 |
| TLH5 0-60 | 51118 | 44.0 | 20 | 11,000 (5) | 5,000 | 0- 2 3/8 | 0- 60 |
| TLH5 0-150 | 51128 | 93.7 | 42.6 | 11,000 (5) | 5,000 | 0- 5 7/8 | 0-150 |
| TLH10 0-60 | 51138 | 70 | 32 | 22,000 (10) | 10,000 | 0- 2 3/8 | 0- 60 |
| TLH10 0-150 | 51148 | 136 | 62 | 22,000 (10) | 10,000 | 0- 5 7/8 | 0-150 |




NK automatic clamps for heavy duty applications

The NK has an automatic locking mechanism when the plate is correctly positioned at the back of the clamps throat.

- A clamp specifically for arduous working conditions
- Well adapted for heavy and abrasive loads
- Lever and clamping jaw protected from impact and wear
- Built with high strength materials
- The locking lever does not stick out so that the clamp may be used on the bare ground
- Permanently attached chain sling with a large oval suspension ring

| Model | Item Number | Weight lbs. | Weight kg | WLL lbs. (t) | WLL kg | Opening inches | Opening mm |
|-------------|-------------|-------------|-----------|--------------|--------|----------------|------------|
| NK1 0-20 | 50288 | 8.8 | 4 | 3,300 (1.5) | 1,500 | 0- 3/4 | 0-20 |
| NK1 20-40 | 50298 | 12.8 | 5.8 | 3,300 (1.5) | 1,500 | 7/8 - 1 1/2 | 20-40 |
| NK1 40-60 | 50308 | 13.2 | 6 | 3,300 (1.5) | 1,500 | 1 5/8- 2 5/16 | 40-60 |
| NK2 0-30 | 50318 | 28.6 | 13 | 6,600 (3) | 3,000 | 0- 1 1/8 | 0-30 |
| NK2 30-60 | 50328 | 33.0 | 15 | 6,600 (3) | 3,000 | 1 3/16- 2 5/16 | 30-60 |
| NK2 60-90 | 50338 | 37.4 | 17 | 6,600 (3) | 3,000 | 2 3/8- 3 1/2 | 60-90 |
| NK3 0-40 | 50348 | 55.0 | 25 | 9,900 (4.5) | 4,500 | 0- 1 1/2 | 0-40 |
| NK3 40-80 | 50358 | 57.2 | 26 | 9,900 (4.5) | 4,500 | 1 5/8- 3 | 40-80 |
| NK3 80-120 | 50368 | 59.4 | 27 | 9,900 (4.5) | 4,500 | 3 3/16- 4 5/8 | 80-120 |
| NK5 0-50 | 50378 | 93.1 | 42.3 | 16,500 (7.5) | 7,500 | 0-2 | 0-50 |
| NK5 50-100 | 50388 | 110.0 | 50 | 16,500 (7.5) | 7,500 | 2-4 | 50-100 |
| NK5 100-150 | 50398 | 132.0 | 60 | 16,500 (7.5) | 7,500 | 4-6 | 100-150 |



*Per pair